




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C02F 1/44, 1/28, 1/42, 1/66, 1/469, 1/58, 1/60, 9/00		A1	(11) International Publication Number: WO 99/50184
			(43) International Publication Date: 7 October 1999 (07.10.99)
(21) International Application Number: PCT/US99/06849 (22) International Filing Date: 29 March 1999 (29.03.99) (30) Priority Data: 09/052,232 31 March 1998 (31.03.98) US (71) Applicant (for all designated States except US): UNITED STATES FILTER CORPORATION [US/US]; 40-004 Cook Street, Palm Desert, CA 92211 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): ARBA, John [US/US]; 111 Kinsbury Avenue, Bradford, MA 01835 (US). WOOD, Jon [US/US]; 41 Homestead, Needham, MA 02194 (US). ZOCCOLANTE, Gary [US/US]; 27 South Street, Plymouth, MA 02360 (US). GANZI, Gary, C. [US/US]; 74 Valleyfield Street, Lexington, MA 02173 (US). (74) Agent: GANZI, Gary, C.; United States Filter Corporation, 10 Technology Drive, Lowell, MA 01851 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: WATER TREATMENT SYSTEM AND PROCESS COMPRISING PH-ADJUSTMENT



(57) Abstract

A water treatment system (50) and process for removing weakly ionized and/or organic materials from the water by intra-system pH adjustment. An exemplary embodiment of the system includes an inlet through which a feedstream (52) passes into a first chemical treating unit (58) wherein the pH of the feedstream is maintained below about 7 to substantially reduce a concentration of weakly basic components in the water by chemical conversion to a more ionized state. A first water treatment unit (62) is positioned downstream of the first chemical treating unit (58) to substantially remove ionized components in the stream, and produce a first product stream. In various embodiments, the first water treatment unit can be selected from the group consisting of a media filter unit, a water softener unit, a dechlorination unit, and combinations thereof. The first product stream is treated downstream of the first water treatment unit (62) in a second chemical treating unit (66) to maintain the pH of the first product stream above about 7 to substantially reduce a concentration of weakly acidic components in the water by chemical conversion to a more ionized state. A second water treatment unit (70) is positioned downstream of the second chemical treating unit (66) to substantially remove the ionized components, and produce a second product stream, which exits the system through a purified water outlet (76) positioned downstream of the second water treatment unit.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WATER TREATMENT SYSTEM AND PROCESS COMPRISING PH-ADJUSTEMENT

BACKGROUND OF THE INVENTION1. Field of the Invention:

5 The present invention relates to a water treatment system and process and, more particularly, to a water treatment system and process for producing purified water for high purity applications.

2. Description of the Related Art:

High purity water is required in many industries such as the chemical industry, the
10 foodstuffs industry, the electronics industry, the power industry, and the pharmaceutical industry. Typically these applications require treatment of a source water supply (such as from a municipal water supply) to reduce the level of contaminants. These treatment techniques can include distillation, filtration, ion exchange, reverse osmosis, photooxidation, ozonation, and combinations thereof.

15 In an effort to decrease biological contaminants in municipal water supplies, especially in warmer environments, the addition of chloramine to municipal water supplies has become commonplace. While effective as a biocidal agent, chloramine becomes a contaminant itself in certain industrial applications requiring high purity water. Furthermore, chloramine is difficult to remove from water without producing other unwanted contaminants
20 such as ammonia. Municipal water supplies can also contain unacceptable levels of dissolved carbon dioxide, boric acid, silicic acid (hydrated silica) and/or organic materials. These weakly ionized and organic materials are also difficult to remove from water.

Nuclear and fossil-fuel power plants, in particular, have stringent water quality requirements to reduce corrosion and scaling and the associated expensive downtimes. In
25 pressurized water reactor nuclear plants, for example, high-purity water is important in reducing corrosion in steam generators. In boiling water reactor nuclear plants, high-purity water is important in maintaining water quality in the nuclear reactor. Traditionally, makeup water treatment systems for power plants have relied almost exclusively on various combinations of filtration, ion-exchange, and reverse osmosis.

30 Similarly, the pharmaceutical industry requires various degrees of purified water for use in drug manufacture, injection of drugs, irrigation, and inhalation. The United States

Pharmacopoeia (USP) lists standards for the various types of water used in the pharmaceutical industry, including purified water, sterile purified water, water for injection, sterile water for injection, sterile bacteriostatic water for injection, sterile water for irrigation, and sterile water for inhalation.

5 While drinking water is not covered by the USP, water that complies with the U.S. Environmental Protection Agency (EPA) drinking water regulations is the prescribed source water for the production of pharmaceutical grade waters. Purified water can be used to process certain drugs, particularly as a cleaning agent for equipment and in the preparation of certain bulk pharmaceuticals. Purified water, according to the USP, must meet almost all of
10 the same purity requirements as water for injection with the exception of bacteria and pyrogen levels. As noted, purified water is produced using drinking water as the source water, which is purified using pretreatment equipment followed by at least one of ion exchange, reverse osmosis, and distillation.

Sterile purified water is not used in any drug that will be introduced directly into the
15 bloodstream. Purified water is made sterile by heating it to a minimum temperature of 121 °C for at least 15 minutes. Water for injection, according to the USP, may be used in the production of certain drugs, also as a rinsing agent for certain equipment and the preparation of certain bulk pharmaceuticals. Water for injection can be introduced directly into a patient's bloodstream and, therefore, must meet all purified water standards and additionally
20 meet endotoxin limits. In the processing of water for injection, a reverse osmosis or distillation unit must be used. Relatedly, sterile water for injection is packaged in volumes not larger than 1 liter and is made sterile as noted above.

Typically, sterile water for injection is used to dilute drugs which will be introduced into the bloodstream. Sterile bacteriostatic water for injection is similar to sterile water for
25 injection that is packaged in volumes not larger than 30 milliliters and to which is added antimicrobial agents. Sterile water for irrigation is used during surgical procedures to flush tissue within the body. Lastly, sterile water for inhalation is similar to sterile water for injection that is used in inhalers and in the preparation of inhalation solutions.

FIG. 1 illustrates a schematic process flow diagram of a prior art water treatment
30 system 10 for producing purified water and/or water for injection for use in pharmaceutical applications. As shown, feedwater, typically municipal drinking water, is fed through line 12



- 3 -

to a media filter unit 14 to remove bulk particulate material. The water is then passed through a water softener 16, most typically an ion exchange unit. The ion exchange unit is typically a sodium-cycle cation exchange unit that is used to remove scale-forming cations such as calcium and magnesium. In addition, water softener 16 serves to remove double and triple charged cations and reduce the tendency for coagulation of colloids that could foul downstream reverse osmosis membranes. The water is then passed through a heat exchanger 18, which is typically used in system 10 if the source water is from a surface water source such as a lake or river.


The water is passed from heat exchanger 18, if used, to a dechlorination unit 20 that includes an activated carbon bed to remove chlorine, which is typically present in the municipal drinking water that serves as the source water for the system. A dechlorination unit is necessary because the most commonly used reverse osmosis membranes, thin film composite polyamide membranes, typically have low tolerance to oxidizing agents such as chlorine. The water is then passed to a cartridge filtration unit 22, which provides a final filtration to protect the reverse osmosis membranes from fouling or other damage caused by relatively large particles generated from upstream equipment. The water is then passed to a reverse osmosis unit 24, which typically removes greater than 98 percent of dissolved substances from the feedwater. Although not shown, a double-pass configuration of reverse osmosis units can be used to achieve high quality purified water. The permeate from the reverse osmosis unit(s) is then passed to a distillation unit 26 for the production of water for injection. A storage tank 28 may also be provided to store the distilled water prior to its use in production and/or packaging in unit 30.

As noted above, municipal drinking water is either chlorinated or chloraminated to control pathogenic microorganisms. In recent years many municipalities have changed methods of water supply disinfection from chlorine to chloramines to reduce the formation of trihalomethanes (THM's), which the EPA currently limits to 100 parts per billion in potable water. THM's are formed by the reaction of chlorine with organic substances. Chloramines are formed by the addition of chlorine, which forms hypochlorous acid, and ammonia to the water. Chloramine form (mono, di, tri) is a function of pH and the chlorine/ammonia ratio, with monochloramine predominating at pH 7 or higher; dichloramine predominating at pH 4 to 5.5; and trichloramine predominating at pH 3 to 4.5 by the following reactions:


- 4 -



5 A dechlorination unit, including an activated carbon bed, is effective for the reduction of free aqueous chlorine by the following reactions:



and has also been used to remove chloramines, with considerably longer contact time, as
10 follows:



The production of both ammonia and nitrogen gas, however, indicates that the activated carbon bed is not sufficient by itself to achieve a low concentration of both chloramine and
15 ammonia. Moreover, ammonia is not effectively removed from water by reverse osmosis treatment.

As government regulations become more stringent and the demand for high purity water continues to grow, new and improved methods of treating municipal water to obtain high purity water are needed. To date, there is no effective method of removing chloramines,
20 as well as weakly ionized species and organic materials, in the same system.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a water treatment system and process for providing high purity water. Advantages of the present invention include its ability to substantially reduce or eliminate the presence of weakly ionized and/or organic materials,
25 including their equilibrium constituents, from water; its ability to effectively remove chloramine from water; and its ability to substantially remove the aforementioned materials while providing high resistivity water.

The system includes an inlet for introducing a feedstream into the system. The feedstream is treated downstream of the inlet in a first chemical treating unit to maintain the
30 pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components in the water by chemical conversion to a more ionized state. A first water

- 5 -

treatment unit is positioned downstream of the first chemical treating unit to substantially remove ionized components in the stream, and produce a first product stream. The first product stream is treated downstream of the first water treatment unit in a second chemical treating unit to maintain the pH of the first product stream above about 7 to substantially
5 reduce a concentration of weakly acidic components in the water by chemical conversion to a more ionized state. A second water treatment unit is positioned downstream of the second chemical treating unit to substantially remove the ionized components, and produce a second product stream. The high purity water is removed from the system through a purified water outlet positioned downstream of the second water treatment unit.

10 In various embodiments, the first water treatment unit can be selected from the group consisting of a media filter unit, a water softener unit, a dechlorination unit, and combinations thereof. The second water treatment unit can be a single reverse osmosis unit, or staged reverse osmosis units wherein a second reverse osmosis unit is positioned downstream of the first reverse osmosis unit and upstream of the purified water outlet. An electrodeionization
15 unit may be used in the water treatment system, in place of or in series with the reverse osmosis unit(s). The system can further include a media filter unit, a water softener unit, and/or a dechlorination unit positioned upstream of the first chemical treating unit. A mixed bed polisher unit can be positioned downstream of the purified water outlet.

In one embodiment of the water treatment system of the present invention, the system
20 includes an inlet for introducing a feedstream into the system. The feedstream is treated downstream of the inlet in a chemical treating unit to maintain the pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components in the water by chemical conversion to a more ionized state. A first reverse osmosis unit is positioned downstream of the chemical treating unit to substantially remove the ionized
25 components in the stream, and produce a first product stream. An electrodeionization unit is positioned downstream of the first reverse osmosis unit to produce a second product stream. A second reverse osmosis unit is positioned downstream of the electrodeionization unit to produce a third product stream. The high purity water is removed from the system from a purified water outlet positioned downstream of the second reverse osmosis unit.

30 In another embodiment of the present invention, a feedstream enters the system through an inlet and is treated in a first reverse osmosis unit to produce a first product stream.

- 6 -

A first water softener unit positioned downstream of the first reverse osmosis unit receives the first product stream and produces a second product stream. The second product stream is treated in a first chemical treating unit positioned downstream of the first water softener unit to maintain the pH of the stream below about 7 to substantially reduce a concentration weakly basic components by chemical conversion to a more ionized state. The pH adjusted second product stream passes through a second reverse osmosis unit to substantially remove ionized components and produce a third product stream, which exits the system through a purified water outlet. Optionally, the system can include a second chemical treating unit positioned upstream of the first reverse osmosis unit to maintain the pH of the feedstream above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state.

In another embodiment, the system includes a water inlet for introducing a feedstream into the system. The feedstream passes sequentially through a media filter unit, a first water softener unit, and a dechlorination unit, before passing through a first chemical treating unit wherein the pH of the feedstream is maintained below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state. A second water softener unit is positioned downstream of the first chemical treating unit to substantially remove ionized components and produce a first product stream. A second chemical treating unit is positioned downstream of the second water softener unit to maintain the pH of the first product stream above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state before the stream enters a first reverse osmosis unit positioned downstream of the second chemical treating unit to substantially remove ionized components and produce a second product stream. The second product stream passes through a second reverse osmosis unit positioned downstream of the first reverse osmosis unit before exiting the system through a purified water outlet.

In another embodiment the water treatment system includes a water inlet for introducing a feedstream into the system and a first chemical treating unit to maintain the pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state. A water softener unit is positioned downstream of the first chemical treating unit to substantially remove ionized components and produce a product stream. A purified water outlet, positioned downstream

- 7 -

of the water softener unit, allows the product stream to exit the system.

In another embodiment of the present invention, a water treatment process is provided. The process includes the steps of a providing a feedstream to be treated and maintaining pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state. The feedstream is then treated in a first water treatment unit to substantially remove ionized components and produce a first product stream. The first water treatment unit can be selected from the group consisting of a media filter unit, a water softener unit, a dechlorination unit, and combinations thereof. The pH of the first product stream is then maintained above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state before the stream is treated in a second water treatment unit to substantially remove the ionized components and produce a second product stream. The second product stream is then removed from the second water treatment unit.

In another embodiment of the present invention, the water treatment process includes the step of maintaining the pH of a feedstream below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state. The feedstream then enters a first reverse osmosis unit to substantially remove ionized components and produce a first product stream. The first product stream is then introduced into an electrodeionization unit to produce a second product stream. The second product stream is treated in a second reverse osmosis unit to produce a third product stream.

In another embodiment, the process includes treating a feedstream in a first reverse osmosis unit to produce a first product stream, before treating the first product stream in a water softener unit to produce a second product stream. The pH of the second product stream is maintained below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state before the stream enters a second reverse osmosis unit, which substantially removes ionized components and produces a third product stream. Optionally, the pH of the feed stream is maintained above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state before treating the stream in the first reverse osmosis unit. To improve output quality, product recovery through the second reverse osmosis unit can be maintained at less than about 90%, flux across the reverse osmosis membranes can be increased, and/or the

- 8 -

temperature of the process stream can be maintained below about 20° C.

In another embodiment, the water treatment process includes the steps of providing a feedstream to be purified, introducing the feedstream into a chemical treating unit to maintain the pH of the feedstream below about 7, and treating the feedstream in an activated carbon filter located immediately downstream of the chemical treating unit to produce a product stream. The product stream is then removed from the activated carbon filter.

BRIEF DESCRIPTION OF THE DRAWINGS

It is to be understood that the following drawings are for the purpose of illustration only and are not intended as a definition of the limits of the invention. In this regard, the foregoing and other objects and features of the present invention will become apparent from the following detailed description when read in light of the following drawings, wherein:

FIG. 1 is a schematic process flow diagram of a prior art water treatment system for producing purified water for pharmaceutical applications;

FIG. 2A is a schematic process flow diagram of one embodiment of a water treatment system of the present invention;

FIG. 2B is a partial schematic process flow diagram of a portion of another embodiment of a water treatment system of the present invention;

FIG. 2C is a partial schematic process flow diagram of a portion of another embodiment of a water treatment system of the present invention;

FIG. 3 is a schematic process flow diagram of another embodiment of a water treatment system of the present invention;

FIG. 4 is a schematic process flow diagram of another embodiment of a water treatment system of the present invention; and

FIG. 5 is a schematic process flow diagram of another embodiment of a water treatment system of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is directed to a water treatment system and process for effectively removing weakly ionic as well as organic materials from feedwater. Such materials, which can include carbon dioxide, ammonia, boron, silica, and the like, are typically difficult to remove while simultaneously producing high purity water.

One embodiment of the water treatment system of the present invention is shown in

- 9 -

FIG. 2A. As shown, a water treatment system 50 is provided in which an input/feedwater stream is introduced into the system through an inlet 52. The feedwater stream typically originates from a municipal water supply, but can also originate from a subterranean or surface water supply, or from precipitation collection.

5 The input/feedwater stream is treated downstream of inlet 52 in a first chemical treating unit 58 to maintain the pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components in the water by chemical conversion to a more ionized state. A first water treatment unit 62 is positioned downstream of first chemical treating unit 58 to substantially remove ionized components in the stream, and produce a first
10 product stream 64. The first product stream is treated downstream of first water treatment unit 62 in a second chemical treating unit 66 to maintain the pH of the first product stream above about 7 to substantially reduce a concentration of weakly acidic components in the water by chemical conversion to a more ionized state. A second water treatment unit 70 is
15 positioned downstream of second chemical treating unit 66 to substantially remove the ionized components, and produce a second product stream 72. The second product stream then exits the system directly through a purified water outlet 76 or, alternatively, passes through a polisher unit 74 to substantially remove remaining contaminants before exiting through purified water outlet 76.

 As shown in FIG. 2A, system 50 can also optionally include a third water treatment
20 unit 54 positioned upstream of first chemical treating unit 58 to pretreat the feedstream before the stream enters unit 58. Third water treatment unit 54 can be selected depending on the types and levels of contaminants found in the feedwater. Such pretreatment units include, for example, a media filter unit, a water softener unit, a dechlorination unit, and combinations thereof. For example, if silica is present in the feed, it can form a colloidal system in the
25 presence of an electrolyte, thereby posing substantial problems to downstream units. Therefore, depending on the pH maintained by first chemical treating unit 58 and on whether silica is present in the feedstream, it may be desirable to position an RO unit (not shown) upstream of first chemical treating unit 58 to remove the bulk of the silica before the feedstream enters unit 58. A preferred pretreatment sequence for most applications is media
30 filtration, followed immediately by softening, followed immediately by dechlorination. "Immediately," as used herein, means having no intermediary treatment units therebetween.

- 10 -

In various embodiments, first water treatment unit 62 can be selected from the group consisting of a media filter unit, a water softener unit, a dechlorination unit, and combinations thereof. The selection of water treatment unit 62 is preferably based upon the discrete circumstances present in the treatment application.

5 Water softener units are traditionally used as a pretreatment method to reduce water hardness (calcium and/or magnesium content) prior to treatment with units containing membranes in order to reduce membrane fouling. Water softener units typically contain resin beads that exchange two sodium ions for every calcium or magnesium ion removed from the "softened" water.

10 Dechlorination units are primarily used to remove chlorine ions from solution. Although it is noted that other types of dechlorination units may be useful in the present invention, the most common type of dechlorination unit is an activated carbon filter. In addition to the ability to remove chlorine, carbon filters provide an additional benefit in their ability to adsorb small organic compounds contained in the water. Carbon's reaction with
15 chlorine is relatively rapid, usually happening within the first minute of contact time. However, carbon is much less effective at removing chloramines from feedwater; more contact time is needed than with chlorine. The efficiency with which carbon reacts with chloramines can be increased by using carbon with a low peroxide number. A carbon's peroxide number is inversely proportional to its degree of catalytic activity. Even using
20 carbon with peroxide numbers below 10, however, will not efficiently remove chloramine from feedwater absent extended contact time. Therefore, the dechlorination unit(s) utilized in the present invention are primarily for the removal of chlorine with a relatively short contact time.

 The media filter units of the present invention preferably contain granular filtration
25 media, such as anthracite, sand, garnet, or combinations thereof. The media can be provided in a single uniform bed, a single mixed bed, or in alternating layers of uniform or mixed composition. The choice of media, number of filter units, and configuration of filter units will depend on factors such as the type of contaminants present and the desired system flow rate. Therefore, the type and configuration of media filter units are selected according to the
30 particular requirements of a given application.

 Second water treatment unit 70 can be selected from the selections available for first

- 11 -

water treatment unit 62 and may include a reverse osmosis (RO) unit. An alternative embodiment of the present invention is shown in FIG. 2B, wherein a system 80 includes second water treatment unit 70 positioned downstream of second chemical treating unit 66, as described above with reference to FIG. 2A. In this embodiment, unit 70 is an RO unit. In addition, a second RO unit 71 is positioned downstream of unit 70 to form a multi-pass RO system, wherein the permeate from unit 70 is fed to unit 71. An electrodeionization unit 73 may also be incorporated into the system either downstream of second RO unit 71 or, alternatively, positioned between units 70 and 71 (not shown). Optionally, system 80 can further include polisher unit 74 to substantially remove remaining contaminants from second product stream 72 before the stream exits through purified water outlet 76.

Another alternative embodiment of the present invention is shown in FIG. 2C, wherein a system 90 includes a second RO unit 65 positioned upstream of second chemical treating unit 66 and second water treatment unit 70. In this embodiment, unit 70 is an RO unit. This configuration passes first product stream 64 through unit 65. The permeate stream from unit 65 is then treated in second chemical treating unit 66, which includes a pH adjustment of the stream to above about 7 to substantially reduce the concentration of weakly acidic components by chemical conversion to a more ionized state. The pH adjusted first product stream is then fed to unit 70 to produce second product stream 72 as noted above. System 90 can also include electrodeionization unit 73 positioned downstream of unit 70, or positioned between unit 65 and second treatment point 66 (not shown), or positioned between second treatment point 66 and unit 70 (not shown). System 90 can also include polisher unit 74 to substantially remove remaining contaminants from second product stream 72 before the stream exits through purified water outlet 76.

As known to those in the art, RO can remove nearly all contaminants from feedwater. The pore structure of RO membranes is such that practically all particles, bacteria and organics greater than 300 Daltons MW are rejected. An RO unit typically contains at least one semi-permeable membrane and a pump for providing hydraulic pressure across the membrane. This hydraulic pressure is applied to the concentrated (contaminated) solution to counteract and overcome the natural osmotic pressure across the membrane. In this manner, purified water is driven from the concentrated solution (feedwater) and collected downstream of the membrane in a storage tank or directed to a point of use.

- 12 -

RO also involves an ionic exclusion process. Only solvent is allowed to pass through the semi-permeable RO membrane, while virtually all ions and dissolved molecules are retained. The semi-permeable membrane rejects salts by a charge phenomena action. That is, the greater the charge, the greater the rejection. Therefore, the membrane is capable of rejecting nearly all strongly ionized components but cannot reject all of the weakly ionized components (which can be removed by a deionization unit).

Different feedwater may require different types of RO membranes. Membranes are commonly manufactured from cellulose acetate, or thin-film composites of polyamide on a polysulfone porous substrate. The proper material for a particular application is determined based on the circumstances at hand.

Electrodeionization units suitable for use in the present invention include, for example, CDI® electrodeionization units, available from United States Filter Corporation, Palm Desert, CA. As is well known, electrodeionization is also referred to as filled-cell electrodialysis and involves a process that effectively deionizes water, while the ion exchange resins positioned within the device are continuously regenerated. This electrochemical regeneration replaces the chemical regeneration of conventional ion exchange systems.

Although electrodeionization units are available in various configurations, such as a spiral design, a plate and frame design, and a circular design, each typically comprises a plurality of cells positioned between two electrodes. Each cell consists of a polymer frame onto which a cation permeable membrane and an anion permeable membrane are positioned on opposite sides. The space in the center of the cell, between the ion-selective membranes, is filled with a bed of ion exchange resins. The cells are separated from one another typically by a screen-type separator.

The feedwater entering the electrodeionization unit is separated into at least three parts. A small percentage flows over the electrodes, a majority of the feed passes through the resin beds in the cells ("diluting compartments"), and the remainder passes along the separators between the cells ("concentrating compartments").

The ion exchange resins capture dissolved ions in the feedwater at the top of the cell. Electric current applied across the module pulls those ions through the ion selective membrane towards the electrodes. Cations are pulled through the cation permeable membrane towards the cathode, and anions through the anion selective membrane towards the anode.


- 13 -

These ions, however, are unable to travel all the way to their respective electrodes since they come to the adjacent ion selective membrane which is of the same charge. This prevents further migrations of ions, which are then forced to concentrate in the concentrating compartments. The ions concentrated in these spaces between the cells are typically flushed
5 out of the system to the drain.

As water passes through the resin beds in the diluting compartments, it is progressively deionized. At the lower end of the diluting compartments, where water is relatively free of ions, splitting of the water occurs in the electric field. This generates hydrogen and hydroxy ions which regenerate the ion exchange resins, effectively eliminating
10 the need for chemical regeneration. Not only is an electrodeionization unit relatively inexpensive to operate, it removes dissolved inorganics (such as carbon dioxide, boron and ammonia) effectively. Therefore, if ammonia is present in the feedwater, it is desirable to include an electrodeionization unit in the system.

The water treatment system of the present invention can further include an ultraviolet
15 (UV) photooxidation unit (not shown) in a variety of positions to lower the level of chlorine, active microorganisms, and organic compounds within the system. A UV unit can be placed in series with any of the components in the system disclosed herein including interstage between two RO units.

UV light in the 254 nm range has been shown to be an effective germicidal treatment
20 for water. The adsorption of UV light by the DNA and proteins in the microbial cell results in the inactivation of the microorganism. A combination of lamps producing UV radiation in both the 185 nm and 254 nm ranges has been shown to be effective in photooxidating organic compounds. Irradiation with UV light in the 185 nm range has been shown to have beneficial effects on chlorine removal. In this regard, it is believed that UV irradiation removes free
25 chlorine from water by the following free radical mechanism:



The water treatment system of the present invention can further include polisher unit

- 14 -



74, such as a mixed bed polisher unit, positioned downstream of second water treatment unit 70. A polisher unit is designed to remove residual traces of impurities from water already treated by other means (such as RO or deionization). A typical polishing system may consist of activated carbon, mixed-bed deionization, organic scavenging mixtures, ultra-fine
5 filtration, or a combination thereof. Specific applications may require ultrafiltration and/or ultraviolet photooxidation units within the polisher unit.

In a preferred embodiment, first chemical treating unit 58 and second chemical treating unit 66 introduce a first chemical treating agent and a second chemical treating agent, respectively, into the feedstream and first product stream 64, respectively. Chemical
10 introduction can be by any conventional method, such as direct metered injection, direct valve injection, or bypass valve polishing. A preferred method of introduction is controlled injection, whereby the system pH is continuously monitored by sensors (not shown) at measuring points downstream of unit 58 and unit 66 respectively. The sensors, which provide an electrical signal corresponding to the pH of the process stream at the measuring points, can
15 be placed in communication with injection controllers located within units 58, 66. The controllers perform the calculations necessary to meter the flow of chemical treating agent into the process stream. In this manner the preferred pH values can be constantly maintained at the proper locations in the water treatment system. One commercially available controller is the Red Lion™ Model PCU proportional integral/derivative controller, available from Red
20 Lion Controls, Inc., York, Pennsylvania.

The pH values to be maintained in the feedstream and first product stream will depend on the types of contaminants present. It will be appreciated that certain, otherwise difficult to remove, weakly ionized compounds will become more highly ionized in acidic or alkaline environments, therefore, becoming more easily removable by water treatment units 62, 70.
25 For example, as noted above, chloramine decomposes on carbon, forming nitrogen gas, ammonium and ammonia. Ammonia is a weak base and is ionized (as ammonium ion) at low pH levels. The first chemical treating agent is introduced in sufficient concentration to maintain the pH of the feedstream below about 7; and, most preferably, into the range of about 6.0 to about 6.5. Virtually all ammonia is converted to ammonium at pH 6.5. However,
30 at a pH of about 5.5, significant amounts of carbon dioxide are present because reduction of the pH will add hydronium ions to the solution, forcing the equilibrium associated with

- 15 -

carbon dioxide and bicarbonate to the left according to the following reactions:



At a pH of 5.5 nearly 83% of the total carbonate present in the treatment stream is in the form of carbon dioxide. Thus, significant deviation from the preferred ranges set out above will result in either minimal ammonia conversion or increased levels of carbon dioxide.

The second chemical treating agent is introduced in sufficient concentration to bring the pH of the first product stream above about 7; and, most preferably, into the range of about 7.5 to about 8.5. Substantially all carbon dioxide is converted to bicarbonate at pH 8.3.

Because higher pH values favor the formation of ammonia from residual ammonium ions, it is desirable to keep the pH as low as possible while ensuring that carbon dioxide to bicarbonate conversion is achieved. If these parameters are not observed, it is possible that excess ammonia gas formed at the higher pH value will become even more concentrated following any subsequent treatment of the second product stream 64 such as with an RO unit.

However, some weakly ionized (or non-ionized) compounds, such as silica, are not normally ionized below a pH of about 9.0. Therefore, it may be desirable, in certain circumstances, to maintain the pH of the first product stream above about 9.0. In these circumstances, a recirculation loop (not shown), with an inlet positioned downstream of first treatment unit 62 and an outlet positioned upstream of first chemical treating unit 58, may be employed, if necessary, to ensure that substantially all ammonia (if present) has been removed from the feedstream.

Although not shown, it will be appreciated that divert valving and/or recycle loops can be added to any combination of units described herein. For example, depending on the types and levels of contaminants present in the feedstream, it may be desirable to divert first product stream 64 to a point of use without allowing stream 64 to pass to downstream units 66, 70. Likewise, it may be desirable to include one or more recycle loops, for example, as noted above regarding the presence of ammonia and silica.

In another alternative embodiment of the present invention, as depicted in FIG. 3, a water treatment system 100 is provided in which an input/feedwater stream is introduced into the system through water inlet 52. The feedstream passes through chemical treating unit 58 where the pH of the stream is maintained below about 7 to substantially reduce the

- 16 -

concentration of weakly basic components by chemical conversion to a more ionized state. The pH adjusted feedstream then passes through a first reverse osmosis unit 101 positioned downstream of unit 58 to substantially remove ionized components and produce a first product stream 102. The first product stream then passes through an electrodeionization unit 103 positioned downstream of first reverse osmosis unit 101 to produce a second product stream 104. The second product stream is treated in a second reverse osmosis unit 105 to produce a third product stream 106, which exits the system directly, through purified water outlet 108, or, alternatively, passes through polisher unit 107 to substantially remove remaining contaminants before exiting through purified water outlet 108. Optionally, the system can further include water treatment unit 54 positioned upstream of chemical treating unit 58 to pretreat the feedstream before the stream enters unit 58. As noted above, water treatment unit 54 can be selected depending on the types and levels of contaminants found in the feedwater.

In another alternative embodiment of the present invention, as depicted in FIG. 4, a feedstream enters a water treatment system 110 through inlet 52 and is treated in a first reverse osmosis unit 116 to produce a first product stream 117. A water softener unit 118, positioned downstream of first reverse osmosis unit 116, receives first product stream 117 and produces a second product stream 120. The second product stream is treated in a first chemical treating unit 122 positioned downstream of first water softener unit 118 to maintain the pH of the stream below about 7 to substantially reduce the concentration weakly basic components by chemical conversion to a more ionized state. The pH adjusted second product stream passes through a second reverse osmosis unit 126 to substantially remove ionized components and produce a third product stream 128, which exits system 110 through a purified water outlet 76.

Optionally, the system can include a second chemical treating unit 112 positioned upstream of first reverse osmosis unit 116 to maintain the pH of the feedstream above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state. Optionally, the system can further include water treatment unit 54 positioned upstream of second chemical treating unit 112 (if provided) and/or first reverse osmosis unit 116 to pretreat the feedstream. As noted above, water treatment unit 54 can be selected depending on the types and levels of contaminants found in the feedwater.

- 17 -

Water softener unit 118 can contain cation exchange resins, in the form of spherical beads or the like, to lower the ionized components in the permeate of first RO unit 116 by an ion exchange mechanism. Specifically, the cation exchange resin can be in sodium form, resulting in the exchange of a sodium ion for other ions encountered in the permeate. It has
5 been determined that by placing the ion exchange softener unit between the RO units, the ion removal efficiency of the softener unit is increased approximately 68% to 98% relative to systems incorporating an ion exchange softener upstream of the first RO unit.

To increase the purity of the final product of any of the embodiments discussed above that incorporate a two-stage RO system, product water recovery (PWR) through the second
10 RO unit is preferably less than about 90%; more preferably less than about 75%; and, most preferably less than about 50%. PWR is an art-recognized parameter that quantitatively describes RO performance and is generally defined as follows:

$$\text{PWR} = \frac{\text{Product water flowrate}}{\text{Feedwater flowrate}} \times 100$$

15 A typical RO unit includes a plurality of modules. Each module comprises a pressure vessel housing a plurality of either spiral-wound or hollow-fiber membrane elements. The preferred PWR can be achieved by connecting modules in parallel and/or by staging the retentate stream in an array of decreasing number of modules (i.e. a tapered design), whereby the retentate can be directed to a recirculation point upstream of the second RO unit. It is believed
20 that lowering the PWR lowers the load immediately upstream of the RO membrane, resulting in an increase in the membrane's rejection efficiency.

If at least one RO unit is used in the system, the feedwater to the first RO unit is preferably maintained at a temperature less than about 20° C, more preferably less than about 15° C, and most preferably less than about 10° C. If two or more RO units are used in the
25 system, the feedwater to one or more of the downstream RO units is preferably maintained at a temperature less than about 20° C, more preferably less than about 15° C, and most preferably less than about 10° C. In these temperature ranges, the optimum pH for the conversion of ammonia to ammonium is between about 7 and 8, and the solubility of most contaminants decreases as solvent temperature decreases. The feedwater temperature can be
30 readily controlled with a heat exchanger, chiller, or other cooling unit, positioned upstream of the first RO unit. If desired, cooling units can be added downstream of the first RO unit to

maintain the feedwater to additional RO units within these preferred ranges.

To further increase the purity of the final product of the embodiments incorporating two-stage RO, the flux across the membranes of the first RO unit and/or the second RO unit can be maintained such that the ratio of solids to liquid in the permeate stream decreases.

- 5 Flux is the rate of fluid flow across an RO membrane according to the following relationship:

$$\text{Flux} = V/A \cdot T$$

- wherein V is the volume of permeate produce, A is the area of the membrane, and T is a unit of time. Typically, this relationship is expressed as gallons of permeate/square feet of membrane-day (gfd). In preferred embodiments, the flux across the membranes of the first RO unit and/or the second RO unit are maintained above about 15 gfd and about 22 gfd, respectively. The permeation rate of most solids through each RO unit is not affected by increased flux. Therefore, the ratio of solids to liquid in the permeate stream decreases with increased flux.
- 10

- Although the flux of each RO unit can be readily controlled by varying one or more system parameters, such as pH, operating pressure, PWR, reject flow, and temperature, the primary parameters are operating pressure and temperature. Preferred ranges of PWR and temperature have been discussed above. When operating within these preferred parameters, flux can be primarily a function of system operating pressure. In this regard, the average operating pressure across both RO units is preferably maintained above about 200 lb_f/in², more preferably above about 300 lb_f/in² by in-line pumps and/or valving.
- 15
- 20

- In another alternative embodiment of the present invention, as shown in FIG. 5, a feedstream enters water treatment system 130 through inlet 52. The feedstream is treated in a chemical treating unit 132 to maintain the pH of the feedstream below about 7, to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state. The treated feedstream is then treated in an activated carbon filter 134 located immediately downstream of chemical treating unit 132 to produce a product stream 136. The product stream is then removed from filter 134.
- 25

- If monochloramine is present in the feedstream of system 130, the pH of the feedstream is preferably maintained between 4.0 and 4.5 to convert the monochloramine to dichloramine. The carbon then dissociates the dichloramine to nitrogen, rather than ammonia and ammonium, which, in many applications, can pass through downstream equipment
- 30

without adversely affecting water quality.

The present invention will be further illustrated by the following examples, which are intended to be illustrative in nature and are not to be construed as limiting the scope of the invention.

5

EXAMPLE 1

To determine the comparative effectiveness of the present invention in treating feedwater containing chloramines and carbon dioxide, the following tests were conducted. Four discrete water treatment systems were supplied with feedwater from the same contaminated source. When the systems reached steady state, the final product of each system
10 was analyzed for resistivity/purity. Also, RO feed conductivity was measured immediately upstream of the first RO unit.

The supply water, which was municipal water obtained in Lowell, Massachusetts, arrives at a point of use in the municipal water system with a conductivity value of approximately $100\mu\text{S}/\text{cm}$. The supply water was further treated with multimedia filtration,
15 softening, and ultrafiltration (UF) prior to use.

Sodium bicarbonate was added to the feedstream to simulate various levels of alkalinity, while sodium hypochlorite and ammonium chloride were injected into the feedstream to form monochloramine at a predetermined concentration of 1.5 ppm. Static mixers were added to the feedstream line in series with the contaminant injectors to ensure
20 proper distribution of contaminants.

The basic components common to all four test systems were:

- 1) pretreatment = 2.1 cu. ft. activated carbon bed and a $5\mu\text{m}$ cartridge filter;
- 2) a first water treatment unit = 1.2 cu. ft. water softener; and
- 25 3) a second water treatment unit = a two-pass RO system with a 55 gallon interstage storage tank and a heat exchanger in the recycle path of the second pass RO.

In each test run, the RO system was configured to recover 50% of the feedwater on the first pass and 90% on the second pass, for an overall recovery of 45%. Each pass
30 consisted of one 4820HR 4x40 thin film composite cartridge, available from Fluid Systems,

Inc., San Diego, CA, and was operated in a recirculate mode, with only a bleed stream from each stage and the final product stream exiting the system. Operating pressures were maintained at 200 lb_f/in² per RO pass. The temperature of the feedwater supply was 8 to 10°C, while RO pass temperatures were 15 to 18°C.

5 System 1 consisted only of the basic components without any pH adjustment of the product streams. System 2 consisted of the basic components with the addition of a caustic feed immediately upstream of the first RO pass. System 3 consisted of the basic components with the addition of interstage caustic injection in the RO system, which is substantially similar to the process disclosed by Pittner in U.S. Patent No. 4,575,049, which is incorporated
10 herein in its entirety by reference. System 4 was an exemplary embodiment of the present invention, and consisted of the basic components with the addition of acid injection immediately upstream of the softener and interstage caustic injection in the RO system.

 All pH adjustments in Systems 2-4 were made with 10 gpd LMI™ chemical feed injectors, available from Liquid Metronics, a Division of Milton Roy, Inc., Acton, MA, and
15 Prominent™ chemical metering pumps, available from Prominent, Inc., Pittsburgh, PA. Permeate resistivity and RO feed conductivity measurements were taken with a 200CR meter, while RO feed pH measurements were taken with a 200pH meter, both available from Thornton, Inc., Waltham, MA.

 The acid used in System 4 was 36 to 38% electronics grade hydrochloric acid, which
20 was further diluted to 0.1 to 0.2%, by volume, before injection. The caustic injected into Systems 2-4 was food grade sodium hydroxide pellets dissolved in water to a concentration of 0.2 to 0.8%, by weight. When necessary, feedwater alkalinity was increased by adding food grade sodium bicarbonate dissolved in water to a concentration of 8.0%, by weight.

 Table 1 below details the results of the comparative effectiveness of each system. Low
25 alkalinity was considered to be the alkalinity of the UF softened water without bicarbonate addition. Conductivity of this feedwater ranged from 72 to 218 μS/cm, with pH ranging from 7.09 to 7.80. High alkalinity was considered to be the UF softened water with the addition of 100 ppm as calcium carbonate. Conductivity of this feedwater ranged from 300 to 359 μS/cm, with pH ranging from 7.9 to 8.4.

Table 1

	Low Alkalinity	Low Alkalinity	High Alkalinity	High Alkalinity
	<u>0.0 ppm NH₂Cl</u>	<u>1.5 ppm NH₂Cl</u>	<u>0.0 ppm NH₂Cl</u>	<u>1.5 ppm NH₂Cl</u>
SYSTEM 1	0.65 - 1.2 ¹ 132 - 135 ²	0.8 130	0.3 - 0.65 337	0.45 -
SYSTEM 2	3.2 97	0.35 218	2.4 - 3.4 345 - 359	0.9 350
SYSTEM 3	2.5 72	2.25 102	- -	- -
SYSTEM 4	3.0 88	3.1 133 - 140	1.1 - 2.8 ~330	1.4 - 3.1 ~330

As shown in Table 1, the permeate from System 4 had a higher resistivity in both low and high alkalinity environments (i.e., 3.1 and 1.4 - 3.1 Mohm-cm, respectively) when low concentrations of monochloramine (i.e., 1.5 ppm NH₂Cl) were present in the feedwater. Thus, System 4 is superior to Systems 1-3 in producing high quality water when monochloramine is present in the feed.

EXAMPLE 2

To determine the effect of the addition of an electrodeionization unit to the present invention, the configuration of System 4 of Example 1 was fitted with a ten cell pair CDI[®] electrodeionization unit, available from United States Filter Corporation, Palm Desert, California. The electrodeionization unit was positioned downstream of the 2-pass RO unit in order to treat the RO permeate stream. The feedwater was from the same source as in Example 1. The system was activated and allowed to reach steady state. The resistivity of the system product water at steady state was consistently over 17 Mohm-cm, with a product flow rate of 0.7 gpm and 83% PWR. Therefore, the addition of an electrodeionization unit to System 4 downstream of the RO unit resulted in the consistent production of high purity

¹ Permeate Quality, Mohm-cm

² RO Feed Conductivity, μ S/cm

water notwithstanding the variability of RO pretreatment.

EXAMPLE 3

To further evaluate the system used in Example 2 when ammonia was present in the water, 1 ppm of dilute household ammonia was injected into a system having the same configuration as that used in Example 2. The ammonia was injected downstream of the 2-pass RO unit and upstream of the electrodeionization unit. The RO unit was configured to provide an 88% PWR. The concentration of ammonia in the electrodeionization feed was 0.51 to 1.70 ppm, with a pH of 8.8 to 9.6 and a conductivity of 6.1 to 9.3 $\mu\text{S}/\text{cm}$. The feedwater to the system was from the same source as in Examples 1 and 2.

The system was activated and allowed to reach steady state. The resistivity of the system product water at steady state ranged from 17.2 to 18.0 Mohm-cm. Thus, notwithstanding the presence of ammonia which generally passes through an RO unit, the addition of an electrodeionization unit to the system results in consistent production of high resistivity water.

It will be understood that each of the elements described above, or two or more together, may also find utility in other applications differing from those described above. While the invention has been illustrated and described as embodied in a water treatment system and process, it is not intended to be limited to the details shown, since various modifications and substitutions may be made without departing in any way from the spirit of the present invention. For example, other conventional water treatment methods may be used in conjunction with the present invention as dictated by specific system requirements. Such methods may include ultrafiltration and ozonation as well as the addition of recycle loops to any of the units described herein.

Further modifications and equivalents of the invention herein disclosed will occur to persons skilled in the art using no more than routine experimentation, and all such modifications and equivalents are believed to be within the spirit and scope of the invention as defined by the following claims.

What is claimed is:

CLAIMS

1. A water treatment system comprising:
 - an inlet for introducing a feedstream into the system;
 - a first chemical treating unit positioned downstream of the inlet to maintain the pH of
 - 5 the feedstream below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state;
 - a first water treatment unit selected from the group consisting of a media filter unit, a water softener unit, a dechlorination unit, and combinations thereof, positioned downstream of the first chemical treating unit to substantially remove ionized components and produce a
 - 10 first product stream;
 - a second chemical treating unit positioned downstream of the first water treatment unit to maintain the pH of the first product stream above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state;
 - a second water treatment unit positioned downstream of the second chemical treating
 - 15 unit to substantially remove ionized components and produce a second product stream; and
 - a purified water outlet positioned downstream of the second water treatment unit.
2. The water treatment system of claim 1, wherein the first water treatment unit is a water softener unit.
3. The water treatment system of claim 1, wherein the second water treatment unit is a
- 20 first reverse osmosis unit.
4. The water treatment system of claim 3, further comprising a cooling unit for lowering the temperature of the first product stream before said stream enters the first reverse osmosis unit.
5. The water treatment system of claim 3, further comprising a second reverse osmosis
- 25 unit positioned downstream of the first reverse osmosis unit and upstream of the purified water outlet.

6. The water treatment system of claim 3, further comprising a second reverse osmosis unit positioned between the first water treatment unit and the second chemical treating unit.
7. The water treatment system of claim 6, further comprising a dechlorination unit
5 positioned upstream of the first chemical treating unit.
8. The water treatment system of claim 7, further comprising a media filter unit positioned upstream of the dechlorination unit.
9. The water treatment system of claim 8, further comprising a water softener unit positioned downstream of the media filter unit and upstream of the dechlorination unit.
- 10 10. The water treatment system of claim 1, wherein the second water treatment unit is an electrodeionization unit.
11. The water treatment system of claim 3, further comprising an electrodeionization unit positioned downstream of the first reverse osmosis unit.
12. The water treatment system of claim 5, further comprising an electrodeionization unit
15 positioned downstream of the first reverse osmosis unit.
13. The water treatment system of claim 6, further comprising an electrodeionization unit positioned downstream of the first reverse osmosis unit.
14. The water treatment system of claim 1, further comprising a reverse osmosis unit positioned between the inlet and the first chemical treating unit.
- 20 15. A water treatment system comprising:
an inlet for introducing a feedstream into the system;
a chemical treating unit positioned downstream of the inlet to maintain the pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components

- 25 -

by chemical conversion to a more ionized state;

a first reverse osmosis unit positioned downstream of the chemical treating unit to substantially remove ionized components and produce a first product stream;

an electrodeionization unit positioned downstream of the water treatment unit to
5 produce a second product stream;

a second reverse osmosis unit positioned downstream of the electrodeionization unit to produce a third product stream; and

a purified water outlet positioned downstream of the second reverse osmosis unit.

16. The water treatment system of claim 15, further comprising a cooling unit for
10 lowering the temperature of the feedstream before said stream enters the first reverse osmosis unit.

17. The water treatment system of claim 15, further comprising a cooling unit for lowering the temperature of the second product stream before said stream enters the second reverse osmosis unit.

15 18. The water treatment system of claim 15, further comprising a dechlorination unit positioned upstream of the chemical treating unit.

19. The water treatment system of claim 18, further comprising a media filter unit positioned upstream of the dechlorination unit.

20. The water treatment system of claim 19, further comprising a water softener unit
20 positioned downstream of the media filter unit and upstream of the dechlorination unit.

21. The water treatment system of claim 15, further comprising a third reverse osmosis unit positioned between the inlet and the chemical treating unit.

22. The water treatment system of any of the above claims, further comprising an ion exchange polisher unit positioned downstream of the purified water outlet.

23. A water treatment process comprising the steps of:
providing a feedstream to be treated;
maintaining the pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state;
5 treating the feedstream in a first water treatment unit selected from the group consisting of a media filter unit, a water softener unit, a dechlorination unit, and combinations thereof, to substantially remove ionized components and produce a first product stream;
maintaining the pH of the first product stream above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state;
10 treating the first product stream in a second water treatment unit to substantially remove ionized components and produce a second product stream; and
removing the second product stream from the second water treatment unit.
24. The water treatment process of claim 23, wherein the first water treatment unit is a water softener unit.
- 15 25. The water treatment process of claim 23, wherein the second water treatment unit is a first reverse osmosis unit.
26. The water treatment process of claim 25, further comprising the step of treating the second product stream in a second reverse osmosis unit.
27. The water treatment process of claim 25, further comprising the step of treating the
20 first product stream in a second reverse osmosis unit before maintaining the pH of the first product stream above about 7.
28. The water treatment process of claim 26, wherein the pH of the feedstream is maintained between about 6.0 and 6.5.
29. The water treatment process of claim 26, wherein the pH of the first product stream is

- 27 -

maintained between about 7.5 and 8.5.

30. The water treatment process of claim 26, wherein the pH of the first product stream is maintained above about 9.0.

31. The water treatment process of claim 26, further comprising the step of cooling the
5 first product stream before introducing said stream into the first reverse osmosis unit.

32. The water treatment process of claim 31, wherein the temperature of the first product stream is maintained below about 20° C before being introduced into the first reverse osmosis unit.

33. The water treatment process of claim 32, wherein the temperature of the first product
10 stream is maintained below about 15° C before being introduced into the first reverse osmosis unit.

34. The water treatment process of claim 26, further comprising the step of maintaining a product water recovery through the first reverse osmosis unit at less than about 90%.

35. The water treatment process of claim 34, wherein the product water recovery through
15 the first reverse osmosis unit is maintained at less than about 75%.

36. The water treatment process of claim 35, wherein the product water recovery through the first reverse osmosis unit is maintained at about 50%.

37. The water treatment process of claim 26, further comprising the step of maintaining a flux across a membrane of the first reverse osmosis unit above about 15 gfd.

20 38. The water treatment process of claim 26, further comprising the step of maintaining a flux across a membrane of the second reverse osmosis unit above about 22 gfd.

- 28 -

39. The water treatment process of claim 37, further comprising the step of maintaining a flux across a membrane of the second reverse osmosis unit above about 22 gfd.
40. The water treatment process of claim 23, further comprising the step of treating the feedstream in a dechlorination unit positioned upstream of the first water treatment unit.
- 5 41. The water treatment process of claim 40, further comprising the step of treating the feedstream in a media filter unit positioned upstream of the dechlorination unit.
42. The water treatment process of claim 41, further comprising the step of treating the feedstream in a water softener unit positioned downstream of the media filter unit and upstream of the dechlorination unit.
- 10 43. The water treatment process of claim 23, wherein the second water treatment unit is an electrodeionization unit.
44. The water treatment process of claim 23, further comprising the step of treating the second product stream in an electrodeionization unit.
45. The water treatment process of claim 36, further comprising the step of treating the
15 second product stream in an electrodeionization unit positioned downstream of the second reverse osmosis unit.
46. The water treatment process of claim 27, further comprising the step of treating the second product stream in an electrodeionization unit.
47. The water treatment process of claim 44, wherein the pH of the first product stream is
20 maintained above about 9.0.
48. The water treatment process of claim 23, further comprising the step of treating the feedstream in a reverse osmosis unit before maintaining the pH of the feedstream below about

7.

49. A water treatment process comprising the steps of:

providing a feedstream to be purified;

maintaining the pH of the feedstream below about 7 to substantially reduce a

5 concentration of weakly basic components by chemical conversion to a more ionized state;

treating the feedstream in a first reverse osmosis unit to substantially remove ionized components and produce a first product stream;

treating the first product stream in an electrodeionization unit to produce a second product stream;

10 treating the second product stream in a second reverse osmosis unit to produce a third product stream; and

removing the third product stream from the second reverse osmosis unit.

50. The water treatment process of claim 49, wherein the pH of the feedstream is maintained between about 6.0 and 6.5.

15 51. The water treatment process of claim 49, further comprising the step of cooling the feedstream before introducing said stream into the first reverse osmosis unit.

52. The water treatment process of claim 51, wherein the temperature of the feedstream is maintained below about 20° C before being introduced into the first reverse osmosis unit.

20 53. The water treatment process of claim 52, wherein the temperature of the feedstream is maintained below about 15° C before being introduced into the first reverse osmosis unit.

54. The water treatment process of claim 49, further comprising the step of cooling the second product stream before introducing said stream into the second reverse osmosis unit.

55. The water treatment process of claim 54, wherein the temperature of the second product stream is maintained below about 20° C before being introduced into the second

reverse osmosis unit.

56. The water treatment process of claim 55, wherein the temperature of the second product stream is maintained below about 15° C before being introduced into the second reverse osmosis unit.

5 57. The water treatment process of claim 49, further comprising the step of treating the feedstream in a dechlorination unit positioned upstream of the first reverse osmosis unit.

58. The water treatment process of claim 57, further comprising the step of treating the feedstream in a media filter unit positioned upstream of the dechlorination unit.

59. The water treatment process of claim 58, further comprising the step of treating the
10 feedstream in a water softener unit positioned downstream of the media filter unit and upstream of the dechlorination unit.

60. The water treatment process of claim 49, further comprising the step of treating the feedstream in a third reverse osmosis unit before maintaining the pH of the feedstream below about 7

15 61. A water treatment system comprising:
an inlet for introducing a feedstream into the system;
a first reverse osmosis unit positioned downstream of the inlet to produce a first product stream;
a first water softener unit positioned downstream of the first reverse osmosis unit to
20 produce a second product stream;
a first chemical treating unit positioned downstream of the first water softener unit to maintain the pH of the second product stream below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state;
a second reverse osmosis unit positioned downstream of the first chemical treating
25 unit to substantially remove ionized components and produce a third product stream; and

- 31 -

a purified water outlet positioned downstream of the second reverse osmosis unit.

62. The water treatment system of claim 61, wherein the first water softener unit comprises ion exchange resins in sodium form.
63. The water treatment system of claim 61, further comprising a cooling unit positioned
5 upstream of the first reverse osmosis unit.
64. The water treatment system of claim 61, further comprising a cooling unit positioned upstream of the second reverse osmosis unit.
65. The water treatment system of claim 61, further comprising a second chemical
treating unit positioned upstream of the first reverse osmosis unit to maintain the pH of the
10 feedstream above about 7 to substantially reduce a concentration of weakly acidic
components by chemical conversion to a more ionized state.
66. The water treatment system of claim 65, further comprising a dechlorination unit positioned upstream of the second chemical treating unit.
67. The water treatment system of claim 66, further comprising a media filter unit
15 positioned upstream of the dechlorination unit.
68. The water treatment system of claim 67, further comprising a water softener unit positioned downstream of the media filter unit and upstream of the dechlorination unit.
69. The water treatment system of claim 61, further comprising an electrodeionization
20 unit positioned downstream of the second reverse osmosis unit.
70. The water treatment system of claim 61, further comprising a polisher unit positioned downstream of the second reverse osmosis unit.

- 32 -

71. The water treatment system of claim 61, further comprising an electrodeionization unit positioned upstream of the first reverse osmosis unit.
72. A water treatment process comprising the steps of:
providing a feedstream to be purified;
5 treating the feedstream in a first reverse osmosis unit to produce a first product stream;
treating the first product stream in a water softener unit to produce a second product stream;
maintaining the pH of the second product stream below about 7 to substantially
10 reduce a concentration of weakly basic components by chemical conversion to a more ionized state;
introducing the second product stream into a second reverse osmosis unit to substantially remove ionized components and produce a third product stream;
removing the third product stream from the second reverse osmosis unit.
- 15 73. The water treatment process of claim 72, wherein the first water softener unit comprises ion exchange resins in sodium form.
74. The water treatment process of claim 72, further comprising the step of maintaining the pH of the feedstream above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state before treating the
20 feedstream in the first reverse osmosis unit.
75. The water treatment process of claim 72, wherein the pH of the second product stream is maintained between about 6.0 and 6.5.
76. The water treatment process of claim 74, wherein the pH of the feedstream is maintained between about 7.5 and 8.5.
- 25 77. The water treatment process of claim 74, wherein the pH of the feedstream is

- 33 -

maintained above about 9.0.

78. The water treatment process of claim 72, further comprising the step of cooling the feedstream before introducing said stream into the first reverse osmosis unit.

79. The water treatment process of claim 72, further comprising the step of cooling the
5 second product stream before introducing said stream into the second reverse osmosis unit.

80. The water treatment process of claim 79, wherein the temperature of the second product stream is maintained below about 20° C before being introduced into the second reverse osmosis unit.

81. The water treatment process of claim 80, wherein the temperature of the second
10 product stream is maintained below about 15° C before being introduced into the second reverse osmosis unit.

82. The water treatment process of claim 72, further comprising the step of maintaining a product water recovery through the second reverse osmosis unit at less than about 90%.

83. The water treatment process of claim 82, wherein the product water recovery through
15 the second reverse osmosis unit is maintained at less than about 75%.

84. The water treatment process of claim 83, wherein the product water recovery through the second reverse osmosis unit is maintained at about 50%.

85. The water treatment process of claim 72, further comprising the step of maintaining a flux across a membrane of the first reverse osmosis unit above about 15 gfd.

20 86. The water treatment process of claim 72, further comprising the step of maintaining a flux across a membrane of the second reverse osmosis unit above about 22 gfd.

- 34 -

87. The water treatment process of claim 85, further comprising the step of maintaining a flux across a membrane of the second reverse osmosis unit above about 22 gfd.
88. The water treatment process of claim 74, further comprising the step of treating the feedstream in a dechlorination unit positioned upstream of the first reverse osmosis unit.
- 5 89. The water treatment process of claim 88, further comprising the step of treating the feedstream in a media filter unit positioned upstream of the dechlorination unit.
90. The water treatment process of claim 89, further comprising the step of treating the feedstream in a water softener unit positioned downstream of the media filter unit and upstream of the dechlorination unit.
- 10 91. The water treatment process of claim 72, further comprising the step of treating the feedstream in an electrodeionization unit positioned upstream of the first reverse osmosis unit.
92. The water treatment process of claim 72, further comprising the step of treating the third product stream in an electrodeionization unit.
- 15 93. A water treatment system comprising:
an inlet for introducing a feedstream into the system;
a media filter unit positioned downstream of the inlet;
a first water softener unit positioned downstream of the media filter unit;
a dechlorination unit positioned downstream of the first water softener unit;
20 a first chemical treating unit positioned downstream of the dechlorination unit to maintain the pH of the feedstream below about 7 to substantially reduce a concentration of weakly basic components by chemical conversion to a more ionized state;
a second water softener unit positioned downstream of the first chemical treating unit to substantially remove ionized components and produce a first product stream;
25 a second chemical treating unit positioned downstream of the second water softener

- 35 -

unit to maintain the pH of the first product stream above about 7 to substantially reduce a concentration of weakly acidic components by chemical conversion to a more ionized state;

a first reverse osmosis unit positioned downstream of the second chemical treating unit to substantially remove ionized components and produce a second product stream;

5 a second reverse osmosis unit positioned downstream of the first reverse osmosis unit;
and

a purified water outlet positioned downstream of the second reverse osmosis unit.

94. A water treatment system comprising:

an inlet for introducing a feedstream into the system;

10 a first chemical treating unit positioned downstream of the inlet to maintain the pH of
the feedstream below about 7 to substantially reduce a concentration of weakly basic
components by chemical conversion to a more ionized state;

a water softener unit positioned downstream of the first chemical treating unit to
substantially remove ionized components and produce a product stream; and

15 a purified water outlet positioned downstream of the first water treatment unit.

95. A water treatment process comprising the steps of:


providing a feedstream to be purified;

maintaining the pH of the feedstream below about 7;

treating the feedstream in an activated carbon filter to produce a product stream; and

20 removing the product stream from the activated carbon filter.

1/4

FIGURE 1
(PRIOR ART)

2/4

FIGURE 2A





FIGURE 2B



3/4

FIGURE 2C





FIGURE 3



4/4

FIGURE 4





FIGURE 5



INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/06849

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C02F1/44 C02F1/28 C02F1/42 C02F1/66 C02F1/469
C02F1/58 C02F1/60 C02F9/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C02F B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 018, no. 307 (C-1211), 13 June 1994 & JP 06 063549 A (KURITA WATER IND LTD), 8 March 1994	1-3,5, 23-26, 29,30,94
Y	see abstract; figure	6,11-13, 40-42,93
X	PATENT ABSTRACTS OF JAPAN vol. 016, no. 338 (C-0965), 22 July 1992 -& JP 04 100589 A (NOMURA MAIKURO SAIENSU KK), 2 April 1992	15,22,49
Y	see abstract; figure	6,11-13, 18-20, 57-59
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

2 July 1999

Date of mailing of the international search report

13/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ruppert, G

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/06849

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 576 752 A (SMITH) 5 January 1994	18-20, 40-42, 57-59, 93
A	see column 3, line 23 - line 41; figure 1 ---	7-9
X	US 5 246 586 A (BAN ET AL) 21 September 1993 see column 3, line 45 - line 66; figure 1 ---	94
X	US 4 695 386 A (BERRY) 22 September 1987 see claims 1, 19 ---	95
P, X	PATENT ABSTRACTS OF JAPAN vol. 099, no. 003, 31 March 1999 & JP 10 314735 A (KURITA WATER IND LTD), 2 December 1998 see abstract; figure ---	1, 3, 5, 23, 25, 26, 28, 29, 95
A	WO 97 05945 A (ZENON ENVIRONMENTAL INC ;COLLENTRO WILLIAM V (US); COLLENTRO ANDRE) 20 February 1997 ---	61, 72
A	EP 0 051 104 A (OPBERGEN JOSEF GMBH & CO) 12 May 1982 ---	61, 72
A	PATENT ABSTRACTS OF JAPAN vol. 097, no. 007, 31 July 1997 & JP 09 057261 A (JAPAN ORGANO CO LTD), 4 March 1997 see abstract; figure ---	
A	US 4 574 049 A (PITTNER) 4 March 1986 ---	
A	GB 2 309 222 A (ORGANO CORP) 23 July 1997 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PC1/US 99/06849

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0576752 A	05-01-1994	US 5174901 A	29-12-1992
US 5246586 A	21-09-1993	JP 5169061 A	09-07-1993
		DE 4222586 A	01-07-1993
		KR 9513998 B	20-11-1995
US 4695386 A	22-09-1987	AU 573511 B	09-06-1988
		AU 5054785 A	27-11-1986
		CA 1272309 A	31-07-1990
		CN 1006199 B	27-12-1989
		EP 0202382 A	26-11-1986
		IN 165671 A	02-12-1989
		JP 1986387 C	08-11-1995
		JP 7018114 B	01-03-1995
		JP 61266690 A	26-11-1986
WO 9705945 A	20-02-1997	US 5766479 A	16-06-1998
		EP 0844907 A	03-06-1998
EP 0051104 A	12-05-1982	DE 3041209 A	13-05-1982
US 4574049 A	04-03-1986	AU 568746 B	07-01-1988
		AU 4309385 A	12-12-1985
		BE 902571 A	30-09-1985
		CA 1251145 A	14-03-1989
		DE 3520006 A	05-12-1985
		FR 2565221 A	06-12-1985
		GB 2159810 A,B	11-12-1985
		JP 6000233 B	05-01-1994
		JP 61004591 A	10-01-1986
GB 2309222 A	23-07-1997	JP 9192661 A	29-07-1997
		US 5833846 A	10-11-1998